





1	5-100009	5 Finger Base Plate
1	5-102422	6 Finger Base Plate
2	4-101229	Cam Plate - 5 Finger
2	4-107024	Cam Plate - 6 Finger
3	2-71769	Screw
4	4-100018	Solid Finger
5	4-100019	Lockdown Finger
6	4-102377	Lockdown Screw
7	441286	Calipers
8	463843 (5 Finger)	Solid Finger with Cam Plate
8	5-102721 (6 Finger)	Solid Finger with Cam Plate
9	463842 (5 Finger)	Lockdown Finger with Cam Plate (includes ref# 2,3,5,6, and 10)
9	5-102720 (6 Finger)	Lockdown Finger with Cam Plate (includes ref# 2,3,5, and 10)
10	4-101250	Screw
11	262468	Hex Style Lockdown – Not used for Art50/500 and Round Shaft AM26
12	8-11100046	Finger Extension Kit
13	4-102566	Lockdown Finger for 8-11100046
14	8-11100284	Plastic Protection Caps (Qty 12)

Photo	Code	Description	Use
	8-11100244	"SHORT" stud kit – 20mm	To reduce the distance between the wheel to the mounting surface on the reverse rim flange by 20 mm and reduce flexing
	8-11100245	"SHORT" stud kit – 40mm	To reduce the distance between the wheel to the mounting surface on the reverse rim flange by 40 mm and reduce flexing
	8-11100246	"LONG" stud kit + 25mm	To increase the distance between the wheel to the mounting surface on the reverse rim flange by 25 mm (increasing space between wheel surface and flange)
	8-11100291	Kit with Spherical head studs for new AUDI wheels	For use with wheel fastener holes with spherical seat (specifically requested by Audi)

*Kits only include fingers. Please refer to above for cam plates and bolts

** Standard finger (4-100018 or 4-100019) = 100mm